

LAMINATED SCANTLINGS

Own production Leutershausen

SPECIES	COMPOSITION	SECTION SIZE
AMERICAN SOFTWOODS		
<p>HEMLOCK</p> <p>Mineral streaks and bark pockets as typical for Hemlock, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried</p> <p>Also with PEFC™-certificate available!</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>72 x 86 / 102 / 115 / 145 mm 84 x 86 / 102 / 115 / 145 mm 96 x 86 / 102 / 115 / 145 mm</p>
<p>OREGON PINE</p> <p>mwith i.f.t.-Rosenheim-certificate D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried</p> <p>Also with PEFC™-certificate available!</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>72 x 86 / 102 / 115 / 145 mm 84 x 86 / 102 / 115 / 145 mm 96 x 86 / 102 / 115 / 145 mm</p>
AMERICAN HARDWOODS		
<p>AMERIC. WHITE OAK</p> <p>natural colour differences and partly appearing sapwood not excluded, D4-glue as per EN 204, multiple ply, blockprofile, kiln dried</p> <p>Also with FSC®- or PEFC™-certificate available!</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>63 x 86 / 105 / 115 / 145 mm 72 x 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm</p>
<p>AMERIC. HARD MAPLE</p> <p>D4-glue as per EN 204, multiple ply, blockprofile, kiln dried</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>72 x 86 mm further dimensions as per your inquiry</p>

s = solid layer / fj = jointed layer



All special dimensions or special constructions as per your inquiry!

LAMINATED SCANTLINGS

Import production

SPECIES	COMPOSITION	SECTION SIZE
AMERICAN HARDWOODS		
AMERIC. WHITE OAK natural colour differences and partly appearing sapwood not excluded, D4-glue as per EN 204, multiple ply, blockprofile, kiln dried	s/fj/s s/s/s s/s/fj s/fj/fj	63 x 86 / 105 / 115 / 145 mm 72 x 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm
ASIAN HARDWOODS		
MERANTI D4-glue as per EN 204, multiple ply, blockprofile, kiln dried available qualities: <ul style="list-style-type: none"> • standard quality, weight 450 kg+ • full log production, weight 450 kg+ also with FSC®- and PEFC™-certificat available!	s/fj/s s/s/s	63 x 75 / 86 / 95 / 125 / 145 mm 72 x 75 / 86 / 95 / 105 / 115 / 125 / 145 mm 84 x 75 / 86 / 105 / 115 / 145 mm 86 x 86 / 115 / 125 / 145 mm 96 x 86 / 115 / 145 mm
	fj/fj/fj	63 x 86 / 125 mm 72 x 86 / 105 / 115 / 125 / 145 mm 84 x 86 / 105 / 115 / 125 / 145 mm 96 x 86 / 105 / 115 / 145 mm

s = solid layer / fj = finger jointed layer



All special dimensions or special constructions as per your inquiry!