

LAMINATED SCANTLINGS

Own production Leutershausen

SPECIES	COMPOSITION	SECTION SIZE
---------	-------------	--------------

MODIFIED SOFTWOODS

MÜNCHINGER ACCOYALINE

Accoya® top layers at least 22 mm, random structur (mainly flat grains), the timber may show strong colour variations (grey/black streaks etc.) as typical for Accoya®, Accsys recommends the case of stainless steel screars, ironmongery etc. which can get in contact with the Accoya® timber, PU laminated, not additionally planed after the lamination process (some glue may be seen on the edges of scantlings!)

Available in all layers Accoya® or combined with Pine or Spruce

Also with PEFC™-certificate available!

s/fj/s
s/s/s
s/fj/fj
s/s/fj

further compositions as per your inquiry

72 x 88 / 105 / 115 / 145 mm (3-fach)
84 x 88 / 105 / 115 / 145 mm (3-fach)
94 x 88 / 105 / 115 / 145 mm (4-fach)
further dimensions as per your inquiry

MÜNCHINGER ENERGYLINE

MÜNCHINGER ENERGYLINE SPRUCE

top layers in Spruce, with pin knots and resin pockets as typical for Spruce, in principle defect-free, v. g./semi v. g., middle layer of high-density insulation, Lambda value 0,04 W/m K, on one side with crossband in real Spruce, laminated with PU-glue, multiple ply, blockprofile, kiln dried

Also with PEFC™-certificate available!

s/fj/s
s/s/s
s/fj/fj
s/s/fj
fj/fj/fj
fj70+/fj/
fj70+

72 x 88 / 105 / 115 / 145 mm
84 x 88 / 105 / 115 / 145 mm
96 x 88 / 105 / 115 / 145 mm

s = solid layer / fj = jointed layer



All special dimensions or special constructions as per your inquiry!