

LAMINATED SCANTLINGS

Own production Leutershausen

SPECIES	COMPOSITION	SECTION SIZE
---------	-------------	--------------

MÜNCHINGER ENERGYLINE – ALSO WITH FSC®- OR PEFC™- CERTIFICATE AVAILABLE!

<p>MÜNCHINGER ENERGYLINE PINE</p> <p>top layers in Pine, middle layer of high density insulation, Lambda value 0,04 W/m²K, on one side with crossband in real Pine, laminated with PU-glue, multiple ply, blockprofile, kiln dried</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj fj/fj/fj fj70+/fj/ fj70+</p>	<p>72 x 88 / 105 / 115 / 145 mm 84 x 88 / 105 / 115 / 145 mm 96 x 88 / 105 / 115 / 145 mm</p>
<p>MÜNCHINGER ENERGYLINE SIB. LARCH</p> <p>top layers in sib. Larch, with colour differences as typical for sib. Larch, in principle defectfree, v. g./ semi v. g., middle layer of high-density insulation, Lambda value 0,04 W/m²K, on one side with crossband in real sib. Larch, laminated with PU-glue, multiple ply, blockprofile, kiln dried</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj fj/fj/fj fj70+/fj/ fj70+</p>	<p>72 x 86 / 115 / 145 mm 84 x 86 / 115 / 145 mm 96 x 86 / 115 / 145 mm</p>
<p>MÜNCHINGER ENERGYLINE OREGON PINE</p> <p>top layers in Oregon Pine, in principle defectfree, v. g./semi v. g., middle layer of high-density insulation, Lambda value 0,04 W/m²K, on one side with crossband in real Oregon Pine, laminated with PU-glue, multiple ply, blockprofile, kiln dried</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj fj70+/fj/ fj70+</p>	<p>72 x 86 / 102 / 115 / 145 mm 84 x 86 / 102 / 115 / 145 mm 96 x 86 / 102 / 115 / 145 mm</p>

s = solid layer / fj = jointed layer



All special dimensions or special constructions as per your inquiry!