

LAMINATED SCANTLINGS

Own production Leutershausen

SPECIES	COMPOSITION	SECTION SIZE
EUROPEAN HARDWOODS		
EUROPEAN OAK natural colour differences and partly appearing sapwood not excluded, D4-glue as per EN 204, multiple ply, blockprofile, kiln dried Also with FSC®- and PEFC™-certificate available!	s/fj/s s/s/s s/fj/fj s/s/fj	72 x 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm
	fj/fj/fj	72 x 86 / 115 mm further dimensions as per your inquiry
AFRICAN HARDWOODS		
SIPO MAHOGANY D4-glue as per EN 204, multiple ply, blockprofile, kiln dried Partly available with FSC®-certificate	s/fj/s s/s/s s/fj/fj s/s/fj	72 x 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm further dimensions as per your inquiry
	fj/fj/fj	72 x 86 mm further dimensions as per your inquiry
SAPELE D4-glue as per EN 204, multiple ply, blockprofile, kiln dried	s/fj/s s/s/s s/fj/fj s/s/fj	72 x 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm further dimensions as per your inquiry
	fj/fj/fj	63 x 86 mm 72 x 86 mm further dimensions as per your inquiry

s = solid layer / fj = jointed layer



All special dimensions or special constructions as per your inquiry!

LAMINATED SCANTLINGS

Import production

SPECIES	COMPOSITION	SECTION SIZE
EUROPEAN HARDWOODS		
E. GLOBULUS weight 850 kg+, D4-glue as per EN 204, v.g./semi v.g., small sound knots and silver figures as typical for E. Globulus from Galicia, multiple ply, blockprofile, kiln dried also with FSC®- and PEFC™-certificat available!	s/fj/s s/s/s	72 x 75 / 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm
	fj/fj/fj	72 x 75 / 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm
EUROP. OAK natural colour differences and partly appearing sapwood not excluded, D4-glue as per EN 204, multiple ply, blockprofile, kiln dried	s/fj/s s/s/s s/s/fj s/fj/fj fj/fj/fj	63 x 86 / 105 / 110 / 115 / 120 / 145 mm 72 x 86 / 105 / 110 / 115 / 120 / 145 mm 84 x 86 / 105 / 110 / 115 / 120 / 145 mm 96 x 86 / 105 / 110 / 115 / 120 / 145 mm

D = durchgehende Lage / K = keilgezinkte Lage



All special dimensions or special constructions as per your inquiry!