

# LAMINATED SCANTLINGS

## Own production Leutershausen

SPECIES	COMPOSITION	SECTION SIZE
<b>EUROPEAN SOFTWOODS</b>		
<b>EUROPEAN LARCH</b> with i.f.t.Rosenheim-certificate with colour differences as typical for Larch, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried <b>Also with PEFC™-certificate available!</b>	s/fj/s s/s/s s/fj/fj s/s/fj	72 x 86 mm 84 x 86 mm 96 x 86 mm further dimensions as per your inquiry
	fj/fj/fj fj70+/fj/ fj70+	72 x 86 mm 84 x 86 mm 96 x 86 mm further dimensions as per your inquiry
<b>FIR</b> with colour differences as typical for Fir, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried <b>Also with PEFC™-certificate available!</b>	s/fj/s s/s/s s/fj/fj s/s/fj	63 x 76 / 88 / 95 / 120 mm 72 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 84 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 96 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm
	fj/fj/fj fj70+/fj/ fj70+	63 x 76 / 88 / 95 / 120 mm 72 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 84 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 96 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm
<b>EUROPEAN HARDWOODS</b>		
<b>BEECH</b> D4-glue as per EN 204, produced of light steamed Beech, with natural discolouration as typical for steamed Beech, no guarantee for any warp dependent on the species, multiple ply, blockprofile, kiln dried <b>Also with PEFC™-certificate available!</b>	s/fj/s s/s/s s/fj/fj s/s/fj	72 x 86 mm further dimensions as per your inquiry

s = solid layer / fj = jointed layer



**All special dimensions or special constructions as per your inquiry!**