

LAMINATED SCANTLINGS

Own production Leutershausen

SPECIES	COMPOSITION	SECTION SIZE
EUROPEAN SOFTWOODS		
PINE (REDWOOD) with i.f.t.-Rosenheim-certificate D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried Also with FSC®- or PEFC™-certificate available!	s/fj/s s/s/s s/fj/fj s/s/fj	63 x 76 / 88 / 95 / 120 mm 72 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 84 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 96 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm
	fj/fj/fj fj70+/fj/ fj70+	56 x 76 / 88 / 95 / 120 mm 63 x 76 / 88 / 95 / 120 mm 72 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 84 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 96 x 88 / 95 / 105 / 115 / 125 / 145 mm
SPRUCE (WHITEWOOD) with i.f.t.-Rosenheim-certificate with pin knots and resin pockets as typical for Spruce, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, kiln dried Also with FSC®- or PEFC™-certificate available!	s/fj/s s/s/s s/fj/fj s/s/fj	63 x 76 / 88 / 95 / 120 mm 72 x 88 / 95 / 105 / 115 / 145 mm 84 x 88 / 95 / 105 / 115 / 145 mm 96 x 88 / 95 / 105 / 115 / 145 mm
	fj/fj/fj fj70+/fj/ fj70+	63 x 76 / 88 / 95 / 120 mm 72 x 76 / 88 / 95 / 105 / 115 / 125 / 145 mm 84 x 76 / 88 / 95 / 105 / 115 / 145 mm 96 x 76 / 88 / 95 / 105 / 115 / 145 mm
SIBERIAN LARCH with i.f.t.-Rosenheim-certificate with colour differences as typical for sib. Larch, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried Also with FSC®-certificate available!	s/fj/s s/s/s s/fj/fj s/s/fj	63 x 76 / 88 / 95 / 120 mm 72 x 88 / 105 / 115 / 145 mm 84 x 88 / 105 / 115 / 145 mm 96 x 88 / 105 / 115 / 145 mm
	fj/fj/fj	63 x 76 / 88 / 95 / 120 mm 72 x 88 / 105 / 115 / 145 mm 84 x 88 / 105 / 115 / 145 mm 96 x 88 / 105 / 115 / 145 mm

s = solid layer / fj = jointed layer



All special dimensions or special constructions as per your inquiry!

LAMINATED SCANTLINGS

Import production

SPECIES	COMPOSITION	SECTION SIZE
EUROPEAN SOFTWOODS		
PINE (REDWOOD) D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried also with FSC®- and PEFC™-certificat available!	fj/fj/fj fj50+fj50+	63 x 75 / 86 / 95 / 105 / 115 / 125 / 145 mm 72 x 75 / 86 / 95 / 105 / 115 / 125 / 145 mm 84 x 75 / 86 / 95 / 105 / 115 / 125 / 145 mm 96 x 75 / 86 / 95 / 105 / 115 / 125 / 145 mm
SPRUCE (WHITEWOOD) with Pin knots and resin pockets as typical for Spruce, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, kiln dried also with FSC®- and PEFC™-certificat available!	fj/fj/fj	63 x 75 / 86 / 95 / 120 mm 72 x 75 / 86 / 95 / 105 / 115 / 125 / 145 mm 84 x 75 / 86 / 105 / 115 / 125 / 145 mm 96 x 75 / 86 / 105 / 115 / 125 / 145 mm
SIBERIAN LARCH with colour differences as typical for sib. Larch, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried also with FSC®-certificat available!	s/fj/s	72 x 86 / 115 / 145 mm 84 x 86 / 115 / 145 mm 96 x 86 / 115 / 145 mm
	fj/fj/fj fj50+fj50+ fj90+fj90+	63 x 75 / 86 / 95 / 120 mm 72 x 75 / 86 / 105 / 115 / 125 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 75 / 86 / 105 / 115 / 145 mm

s = solid layer / fj = finger jointed layer



All special dimensions or special constructions as per your inquiry!