

LAMINATED SCANTLINGS

Own production Leutershausen

SPECIES	COMPOSITION	SECTION SIZE
AMERICAN SOFTWOODS		
<p>HEMLOCK</p> <p>Mineral streaks and bark pockets as typical for Hemlock, D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried</p> <p>Also with PEFC™-certificate available!</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>72 x 86 / 102 / 115 / 145 mm 84 x 86 / 102 / 115 / 145 mm 96 x 86 / 102 / 115 / 145 mm</p>
<p>OREGON PINE</p> <p>mwith i.f.t.-Rosenheim-certificate D4-glue as per EN 204, in principle defect free, v. g./semi v. g., multiple ply, blockprofile, kiln dried</p> <p>Also with PEFC™-certificate available!</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>72 x 86 / 102 / 115 / 145 mm 84 x 86 / 102 / 115 / 145 mm 96 x 86 / 102 / 115 / 145 mm</p>
AMERICAN HARDWOODS		
<p>AMERIC. WHITE OAK</p> <p>natural colour differences and partly appearing sapwood not excluded, D4-glue as per EN 204, multiple ply, blockprofile, kiln dried</p> <p>Also with FSC®- or PEFC™-certificate available!</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>63 x 86 / 105 / 115 / 145 mm 72 x 86 / 105 / 115 / 145 mm 84 x 86 / 105 / 115 / 145 mm 96 x 86 / 105 / 115 / 145 mm</p>
<p>AMERIC. HARD MAPLE</p> <p>D4-glue as per EN 204, multiple ply, blockprofile, kiln dried</p>	<p>s/fj/s s/s/s s/fj/fj s/s/fj</p>	<p>72 x 86 mm further dimensions as per your inquiry</p>

s = solid layer / fj = jointed layer



All special dimensions or special constructions as per your inquiry!