

# AVAILABLE STANDARD LENGTHS FOR SPRUCE

## SPRUCE

THICKNESS	72/84 mm	72/84 mm			96 mm	72/84 mm		96 mm
WIDTH	76 mm	88 mm			88 mm	105/115 mm		
STRUCTURE	C/FJ/FJ	C/FJ/FJ	C/FJ/C	C/C/FJ	C/FJ/FJ/C	C/FJ/C	C/C/FJ	C/FJ/FJ/C
6.20 m								
4.00 m	X	X	X	X	X	X	X	X
3.50 m	X	X	X	X	X	X	X	X
3.00 m	X	X	X	X	X	X	X	X
2.80 m	X	X	X	X	X			
2.70 m	X	X	X	X	X			
2.60 m	X	X	X	X	X			
2.50 m	X	X	X	X	X	X	X	X
2.40 m	X	X	X	X	X	X	X	X
2.30 m	X	X	X	X	X	X	X	X
2.20 m	X	X	X	X	X	X	X	X
2.10 m	X	X	X	X	X	X	X	X
2.00 m	X	X	X	X	X	X	X	X
1.90 m	X	X	X	X	X			
1.80 m	X	X	X	X	X	X	X	X
1.70 m	X	X	X	X	X			
1.60 m	X	X	X	X	X	X	X	X
1.50 m	X	X	X	X	X	X	X	X
1.40 m	X	X	X	X	X	X	X	X
1.30 m	X	X	X	X	X	X	X	X
1.25 m	X	X	X	X	X			
1.20 m	X	X	X	X	X	X	X	X
1.15 m	X	X	X	X	X			
1.10 m	X	X	X	X	X	X	X	X
1.05 m	X	X	X	X	X			
1.00 m	X	X	X	X	X	X	X	X
0.95 m	X	X	X	X	X			
0.90 m	X	X	X	X	X	X	X	X
0.85 m	X	X	X	X	X			
0.80 m	X	X	X	X	X	X	X	X
0.75 m	X	X	X	X	X			
0.70 m	X	X	X	X	X			
0.65 m	X	X	X	X	X			
0.60 m	X	X	X	X	X			
0.55 m	X	X	X	X	X			
0.50 m	X	X	X	X	X			

Extra charge due to excessive length

Not in stock, needs to be trimmed

# AVAILABLE STANDARD LENGTHS FOR SPRUCE

SPRUCE				For lifting/sliding door frames			
THICKNESS	72/84 mm		96 mm	65 mm		65 mm	
WIDTH	145 mm			192 mm		215 mm	
STRUCTURE	C/FJ/C	C/C/C	C/FJ/FJ/C	C/FJ/FJ	FJ180+	C/FJ/FJ	FJ180+
6.20 m					x		x
4.00 m	x	x	x	x		x	
3.50 m	x	x	x				
3.00 m	x	x	x	x		x	
2.80 m							
2.70 m							
2.60 m							
2.50 m	x	x	x	x		x	
2.40 m	x	x	x				
2.30 m	x	x	x				
2.20 m	x	x	x				
2.10 m	x	x	x				
2.00 m							
1.90 m							
1.80 m	x	x	x				
1.70 m							
1.60 m	x	x	x				
1.50 m							
1.40 m	x	x	x				
1.30 m							
1.25 m							
1.20 m	x	x	x				
1.15 m							
1.10 m	x	x	x				
1.05 m							
1.00 m	x	x	x				
0.95 m							
0.90 m	x	x	x				
0.85 m							
0.80 m	x	x	x				
0.75 m							
0.70 m							
0.65 m							
0.60 m							
0.55 m							
0.50 m							

*Extra charge due to excessive length*

*Not in stock, needs to be trimmed*